

Product Specification Sheet – 18 x 150 Solid Unfinished

Product	18 x 150 Unfinished Oak
Finish	Unfinished for Finishing 'On Site'
Thickness	18mm
Width	150mm
Length	Random 300-1800mm with average of 750mm. Few lengths over 1200mm because of stringent quality control process.
Moisture Content	8-12%
Construction	Solid TG4 Micro Bevelled 4 Sides End Matched
Length Tolerance	+/- 1.0mm
Width Tolerance	+/- 0.2mm
Thickness Tolerance	+/- 0.15mm
Carton Size	1850 x 160 x 132
M2 Per Carton	2.21
M2 Per Pallet	92.82 (42 cartons)
Grade	Character. Includes 50% A and B Grade, 25% C Grade, and 25% D Grade. This, in our opinion, provides an authentic and natural looking oak floor with sufficient clear boards and boards with character features, to provide the real beauty of an oak floor.
A Grade	Allows live knots no more than 10mm, dead knots repaired with putty no more than 5mm. Sapwood no more than 5% of face area. Allows natural grain and colour difference.
B Grade	Allows live knots no more than 25mm, dead knots repaired with putty no more than 10mm. Sapwood no more than 15% of face area. Allows natural grain and colour difference.
C Grade	Allows dead knots repaired with putty no more than 25mm. Sapwood no more than 30% of face area. Allows natural grain and colour difference.
D Grade	Allows larger dead knots repaired with putty. Sapwood no more than 40% of face area. Allows obvious natural grain and colour difference. Open defects are filled.
Use With Underfloor Heating?	Not Recommended
Product Code	18150UF

↓**Scroll Down For Image**↓



Oak Floors Online – 0845 459 3073