

Product Specification Sheet – 21 x 240 Engineered Unfinished

Product	21 x 240 Single Strip Engineered Oak
Finish	Sanded Unfinished For Finishing 'On Site'
Thickness	21mm
Width	240mm
Length	75% @ 1900mm long, other 25% made up from 610mm, 915mm, and 1220mm lengths
Moisture Content	8-12%
Construction	Engineered TG4 Micro Bevelled 4 Sides End Matched 6mm Oak Wear Layer 15mm Plywood Backing
Length Tolerance	+/- 1.0mm
Width Tolerance	+/- 0.2mm
Thickness Tolerance	+/- 0.15mm
Carton Size	1910 x 250 x 140
M2 Per Carton	2.74
M2 Per Pallet	76.72 (28 cartons)
Grade	Character. Includes 50% A and B Grade, 25% C Grade, and 25% D Grade. This, in our opinion, provides a really authentic and natural looking oak floor with sufficient clear boards and boards with character features, to provide the real beauty of an oak floor.
A Grade	Allows live knots no more than 10mm, dead knots repaired with putty no more than 5mm. Sapwood no more than 5% of face area. Allows natural grain and colour difference.
B Grade	Allows live knots no more than 25mm, dead knots repaired with putty no more than 10mm. Sapwood no more than 15% of face area. Allows natural grain and colour difference.
C Grade	Allows dead knots repaired with putty no more than 25mm. Sapwood no more than 30% of face area. Allows natural grain and colour difference.
D Grade	Allows larger dead knots repaired with putty. Sapwood no more than 40% of face area. Allows obvious natural grain and colour difference. Open defects are filled.
Use With Underfloor Heating?	Suitable but not guaranteed*
Product Code	21240UF

* NB - The reason we cannot guarantee our Engineered flooring above UFH has nothing to do with the quality of our flooring but is because we have no control over what happens after we deliver it. There are extra requirements for this installation situation and because we have no way of ensuring they are implemented, we cannot provide a guarantee. If our UFH fitting guidelines are followed, you will have no problems at all.

↓**Scroll Down For Image**↓



Oak Floors Online – 0845 459 3073